

Expert in safe-working on electrical systems



✓ sales@eintac.com



m www.eintac.com



+44 (0)1376 525606

PART No.

EHV-ASI###

Fully Insulated Adjustable Spanner

DESCRIPTION

- // Made from Chrome-Vanadium Steel, designed to support high torques with minimum wear out, providing greater durability.
- // Finished in TITACROM® a special surface treatment, more corrosion resistant than standard chrome, resistant to impact and friction (non peel off), non-reflecting with very attractive finishing.
- // The insulation provides maximum adherence and safety against unforeseen circumstances.
- // Insulated head and non-conductive adjustment button.

Please note: The Fully Insulated Adjustable Spanner IOOOV (EHV-ASIXXX) can not be homologated as the wheel nut can not be insulated. The safety of the user can not be guaranteed, even though the insulated material fulfils the requirements of the norm EN-60900 regarding the electrical resistance.

INSULATION

Insulated according to IEC 60900 Usable up to IOOOV AC / I5OOV DC

PART NO.	JAW OPENING	LENGTH (mm)	WEIGHT (g)
EHV-ASI200	29	200	370
EHV-ASI250	33	250	620
EHV-ASI300	38	300	1000



These spanners are also available as part of a kit.

The information provided in this document is for general guidance only. The specifications provided are from the manufacturers information. This document is not intended as a substitute for and is not to be used for determining the suitability or reliability of these products for specific user applications. It is the duty of any such user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. EINTAC Ltd shall not be responsible or liable for misuse of the information contained herein.