

Expert in safe-working on electrical systems



✓ sales@eintac.com



**m** www.eintac.com



+44 (0)1376 525606



EHV-SLS###

## Insulated Slotted Screwdrivers

## **DESCRIPTION**

- // Oversized ergonomic, anti-slippery, bi-material handle offers optimal grip for avoiding slippage
- // Chrome-Vanadium-Molybdenum alloy enables 30% higher tightening torque
- // The innovative anti-slippery and magnetic tip system allows an easier and safer positioning of the screwdriver, avoiding undesired slides
- // Type and size double marking allowing easy identification of the desired screwdriver
- // Go-through hole in the handle enables tommy bar use

PART NO.	TIP LENGTH (mm)	TIP WIDTH (mm)	BLADE LENGTH (mm)	WEIGHT (g)
EHV-SLS325	2.5	0.4	75	41
EHV-SLS33I	3	0.4	100	45
EHV-SLS335	3.5	0.4	100	36
EHV-SLS340	4	5.4	125	81
EHV-SLS355	5.5	6.4	125	90
EHV-SLS354	5.5	6.4	150	IIO
EHV-SLS365	6.5	8.4	150	120
EHV-SLS380	8	9.4	175	175
EHV-SLS310	10	11.4	200	243



Insulated according to IEC 60900 Usable up to IOOOV AC / I5OOV DC



These screwdrivers are also available as part of a set or kit.

The information provided in this document is for general guidance only. The specifications provided are from the manufacturers information. This document is not intended as a substitute for and is not to be used for determining the suitability or reliability of these products for specific user applications. It is the duty of any such user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. EINTAC Ltd shall not be responsible or liable for misuse of the information contained herein.