



EINTAC

Expert in **safe-working**
on **electrical systems**

✉ sales@eintac.com

🌐 www.eintac.com

☎ +44 (0)1376 525606



PART No.

EHV-OES4##

Insulated A/F Open-Ended Spanner

DESCRIPTION

- // Designed for work under electricity tension or in proximity of the voltage insulation
- // Made from Chrome-Vanadium steel, designed to support high torques with minimum wear out, providing greater durability
- // PVC insulation provides maximum adherence and safety against possible contingencies

PART NO.	SIZE (inch)	LENGTH (mm)	WEIGHT (g)
EHV-OES404	1/4	90	30
EHV-OES415	9/32	110	30
EHV-OES405	5/16	110	30
EHV-OES416	3/8	127	40
EHV-OES407	7/16	135	45
EHV-OES408	1/2	147	55
EHV-OES409	9/16	147	75
EHV-OES417	5/8	166	100
EHV-OES411	11/16	166	120
EHV-OES412	3/4	176	130
EHV-OES418	13/16	176	180
EHV-OES413	7/8	200	190
EHV-OES419	15/16	226	220
EHV-OES414	1	250	350
EHV-OES420	1 1/8	266	450
EHV-OES421	1 1/4	281	450

INSULATION

Insulated according to IEC 60900
Usable up to 1000V AC / 1500V DC



These spanners are also available as part of a set or customisable kit.

The information provided in this document is for general guidance only. The specifications provided are from the manufacturers information. This document is not intended as a substitute for and is not to be used for determining the suitability or reliability of these products for specific user applications. It is the duty of any such user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. EINTAC Ltd shall not be responsible or liable for misuse of the information contained herein.