

Expert in safe-working on electrical systems



✓ sales@eintac.com



m www.eintac.com



+44 (0)1376 525606



EHV-SSD###

Insulated Socket Screwdriver

DESCRIPTION

- // Oversized ergonomic, anti-slippery, bi-material handle offers optimal grip for avoiding slippage
- // Chrome-Vanadium-Molybdenum alloy enables 30% higher tightening torque
- // The innovative anti-slippery and magnetic tip system allows an easier and safer positioning of the screwdriver, avoiding undesired slides
- // Type and size double marking allowing easy identification of the desired screwdriver
- // Go-through hole in the handle enables tommy bar use

PART NO.	SIZE	BLADE LENGTH (mm)	TOTAL LENGTH (mm)	WEIGHT (g)
EHV-SSD304	4	150	255	100
EHV-SSD305	5	150	255	120
EHV-SSD355	5.5	150	255	120
EHV-SSD306	6	160	275	120
EHV-SSD307	7	175	290	120
EHV-SSD308	8	175	305	187
EHV-SSD309	9	175	305	190
EHV-SSD310	10	175	305	190
EHV-SSD311	II	175	305	220
EHV-SSD312	12	175	305	221
EHV-SSD313	13	175	305	229
EHV-SSD314	14	175	305	230

INSULATION

Insulated according to IEC 60900 Usable up to IOOOV AC / I5OOV DC



These screwdrivers are also available as part of a set or kit.

The information provided in this document is for general guidance only. The specifications provided are from the manufacturers information. This document is not intended as a substitute for and is not to be used for determining the suitability or reliability of these products for specific user applications. It is the duty of any such user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. EINTAC Ltd shall not be responsible or liable for misuse of the information contained herein.